

# BLUEDRAIN BDL – Belt Thickener

High Performance gravity table



# BLUEDRAIN BDL – Belt Thickener

High Performance gravity table

## Technology


The BlueDrain gravity table is a high-performance continuous belt thickener for the pre-dewatering/ thickening of suspensions e.g. sludge from paper production process & other industries. The flocculated sludge is fed through the head box and distributed over the entire working width of the filter belt. Water flows by gravity through the filter belt while the solids in the water are retained & thickened on its surface. Multiple rows of sludge chicanes and a pressure drum before the discharge end of the table improve the dewatering of the sludge layer. The thickened sludge cake is lifted off by a pressure adjustable take-off doctor blade. A shower with flat jet nozzles is cleaning the filter belt in a washing box.

## Features

- Modular Design (width up to 4 m, length up to 12 m) allows adaption to wide range of inlet consistencies and sludge quantities
- Effective belt cleaning with flat jet nozzles (Stamm Shower Pipe)
- Pneumatic belt centering/ tracking system with limit switches
- Pneumatic belt tensioning system to avoid belt slipping
- Multiple chicane rows and floating dewatering roll ensure highest possible thickening efficiency
- Adjustable take-off doctor blade pressure by counterweight system
- Ring Injector – Static mixer & Injection point for efficient polymer mixing achieving lowest possible Chemical Consumption

## Why to buy

- Multiple chicane rows and dewatering roll ensure highest possible thickening efficiency & discharge dryness up to 20% at lowest Chemical consumption
- Low OPEX by long life filtering belt & reliable mechanical components
- 24/7 trouble free operation supported by highly reliable belt tracking and belt tension adjustment system
- Highest Throughput up to 180 bdt/d
- Easy installation due to pre-assembled machine elements and modular design
- Safe and clean operation due to closed frame design & optional covering hood




## Typical & Proven Process

- Thickening/ Pre-Dewatering of thin sludge & reject suspension
  - from Cleaning & Fine Screening
  - with or w/o defined content of excess bio sludge from Effluent Water Treatment
  - from Water Clarification (DAF units, Primary Clarifiers, ...)
  - from De-Inking Plants
- Filtration/ Fibre Recovery Unit for Process Waters
  - White Water from Decor Paper Manufacturing

## See the following Products as well

- Sludge/Reject Pre-Dewatering by ELEPHANT
- COMPAX CFX-F 50,60 & 80
- MINIPRESS MPX 30, 40 & 50
- RSP- Sludge and Fiber Residual Screw Press RSP 1150, 800 & 650
- MSC- Spiral conveyors and related bunker- & container filling- & distribution systems
- POLYMERI Polymer Preparation Unit

## Specifications



	BDL-2X	BDL-2XL	BDL-3X	BDL-3XL	BDL-4X	BDL-4XL
Belt Width [mm]	2000	2000	3000	3000	4000	4000
Installation Width (A) [mm]	2813	2813	3813	3813	4813	4813
Installation Length (B) [mm]	8281	11031	10295	12295	10267	12267
Installation Height (C) [mm]	1658	1658	1658	1658	1615	1615



**Meri Environmental Solutions GmbH**

Bodenseestr. 113  
81243 Munich, Germany  
Tel. +49 89 59 33 44  
info@meri.de

**Voith Meri Environmental Solutions, Inc.**

2620 E. Glendale Avenue  
P.O. Box 1262  
Appleton WI 54911-1262, USA  
Tel. +1 920 734-8485  
info@meriusa.com

**Meri Sistemas e Tecnologia Ltda.**

R. Friedrich von Voith, 825  
São Paulo – SP – 02995-000, Brasil  
Tel. +55 11 3944-6644  
meribrasil@meribrasil.com.br

**Meri Environmental Technology  
(Kunshan) Co.,Ltd.**

Room 203, No.5, Qinghua Tuspark  
Zuchongzhi Road 1666  
Kunshan, Jiangsu PRC, China  
Tel. +86 51 28 68 90 834  
info@meri.cn

[www.meri.de](http://www.meri.de)



**Note:** All product-related data and information in this publication shall serve for information purposes only. They shall not be interpreted or intended to represent any kind of warranty or guarantee. The only legally binding statements are those contained solely within our quotations. Errors and omissions excepted. Technical data are subject to change.