R2S ANAEROBIC REACTOR

R2S ANAEROBIC REACTOR

Technology

The R2S Anaerobic Reactor is a two staged EGSB reactor optimized for high-COD load and calcium-rich wastewater. The R2S transforms organic waste loads in the wastewater anaerobically and produces biogas. Active biosludge pellets, consisting of anaerobic bacteria, have a lot of surface contact and effective interaction with the wastewater due to the high upflow velocity and external and internal recirculation. The optimal surface exchange provides optimal access to degradable waste and nutrients for the bacteria to remove COD Load. Its design enables efficient biogas separation through settlers and gas separation tanks, while ensuring robust pellet retention. Further design details include a conical bottom for sludge removal during operation and adjustable feed distribution. The reactors fully gas tight design prevents odor emissions, corrosion and minimizes sulfur deposits, ensuring long-term reliability and low-maintenance operation.

Features

- High-efficiency process performance & control through external and internal recirculation for stable hydraulic flow and optimized surface exchange distribution
- Enhanced sludge fluidization preventing dead zones and supporting even distribution of flow within the pellet sludge bed
- Integrated gas separation tanks ensuring effective biogas extraction and optimal pellet retention
- Fully gas tight tank design preventing odors, corrosion, and sulfur deposits for a safer environment
- Reliable control system with adjustable feeding pipes a internal & external recirculation for stable performance
- Conical bottom for heavy sludge removal and efficient sediment discharge during operation

Why to buy

- Highest COD reduction and energy recovery as biogas, lowering energy costs and waste treatment fees
- Reduced OPEX with minimal chemical usage and efficient anaerobic sludge management and pellets growth, optimized for low to no caustic consumption
- Requires low maintenance due to few moving parts and clog-free operation
- Ensures stable performance, even during feed variation and reliable heavy sludge removal during operation
- Supports sustainability goals by maximizing biogas production and minimizing waste disposal needs
- Offers space-saving design with compact, tall tanks reducing installation footprint and improving operational flexibility

Typical & Proven Process

- Anaerobic treatment of high-COD wastewater in paper and beverage industries
- Biogas production from calcium-rich effluents with high COD loads
- Efficient sludge management and sludge growth with reduced calcification and maintenance
- Anaerobic effluent treatment in combination with Lime Trap process provides highest lime (calcium carbonate) removal

See the following Products as well

- E2E Anaerobic Reactor
- E2E UASB
- Lime Trap
- Gas Flare
- Gas Buffer
- Desulfurization

Specifications

Size Examples	Diameter (A) [mm]	Height (B) [m]	Tot. Height (C) [m]	Active Volume [m³]
R2S 050(20)	5000	20	23	201
R2S 050(24)	5000	24	27	279
R2S 050(30)	5000	30	33	358
R2S 090(20)	9000	20	23	593
R2S 090(24)	9000	24	27	847
R2S 090(30)	9000	30	33	1102
R2S 115(20)	11500	20	23	916
R2S 115(24)	11500	24	27	1331
R2S 115(30)	11500	30	33	1905

Meri Environmental Solutions GmbH

Bodenseestr. 113

81243 Munich, Germany

Tel. +49 89 59 33 44

info@meri.de

Voith Meri Environmental Solutions, Inc.

2620 E. Glendale Avenue

P.O. Box 1262

Appleton WI 54911-1262, USA

Tel. +1 920 734-8485

info@meriusa.com

Meri Sistemas e Tecnologia Ltda.

R. Friedrich von Voith, 825

São Paulo – SP – 02995-000, Brasil

Tel. +55 11 3944-6644

meribrasil@meribrasil.com.br

Meri Environmental Technology (Kunshan) Co.,Ltd.

Room 203, No.5, Qinghua Tuspark

Zuchongzhi Road 1666

Kunshan, Jiangsu PRC, China

Tel. +86 51 28 68 90 834

info@meri.cn

www.meri.de

Sustainable meri ■ Environmental Solutions

Note: All product-related data and information in this publication shall serve for information purposes only. They shall not be interpreted or intended to represent any kind of warranty or guarantee. The only legally binding statements are those contained solely within our quotations. Errors and omissions excepted. Technical data are subject to change.